

SIMATIC HMI connecting cable for KTPX00(F) Mobile, Length 8 m



Figure similar

| Standards, approvals, certificates                |        |
|---|--------|
| CE mark   | Yes    |
| cULus   | Yes    |
| RCM (formerly C-TICK)                             | Yes    |
| KC approval                                       | Yes    |
| Suitable for safety functions                     | Yes    |
| Ambient conditions                                |        |
| Ambient temperature during operation              |        |
| • min.  | 0 °C   |
| • max.  | 55 °C  |
| Ambient temperature during storage/transportation |        |
| • min.  | -20 °C |
| • max.  | 60 °C  |
| Cables  |        |
| Cable length                                      | 8 m    |
| Maximum tensile load                              | 300 N  |

|                                  |  |
|----------------------------------|--|
| Color of cable sheath            |  |
| • green                          | Yes  |
| Scope of supply                  |  |
| Delivery quantity in pieces      | 1  |
| Other                            |  |
| Merchandise                      | Yes  |
| Manufacturer name                | SIEMENS AG                                     |
| Manufacturer's address           | Gleiwitzerstraße 555, 90475 Nuremberg, Germany |
| Usable in the following products |  |
| • Product 1                      | 6AV2125-2GB*                                   |
| • Product 2                      | 6AV2125-2JB*                                   |
| • Product 3                      | 6AV2125-2DB23*                                 |
| last modified:                   | 11/23/2018                                     |