

HSK-EX E KABELOVÉ VÝVODKY PRO SPECIÁLNÍ POUŽITÍ

HSK-K-MZ-Ex

Metr.




Mezinárodní certifikáty najdete na str. 154/155 nebo na internetu: www.hummel.com.

Materiál	polyamid-AL
Tvarové těsnění	NBR
O-kroužek	NBR
Krytí	IP 68 – 10 bar / IP 69K
Pracovní teplota	-20 °C – 70 °C



II 2G 1D



AG	\varnothing mm	GL mm	H mm	\varnothing mm	Obj. č.
M 16 x 1,5	4–8	15	29	19	1.215.1601.50
M 20 x 1,5	7–12	15	35,5	24	1.215.2001.50
M 25 x 1,5	13–18	11	41	33	1.215.2501.50
M 32 x 1,5	18–25	11	49	42	1.215.3201.50
M 40 x 1,5	22–32	13	58	53	1.215.4001.50
M 50 x 1,5	32–38	13	61,5	60	1.215.5001.50
M 63 x 1,5	37–44	14	62	65/68	1.215.6301.50

HSK-K-MZ-Ex

PG




Mezinárodní certifikáty najdete na str. 154/155 nebo na internetu: www.hummel.com.

Materiál	polyamid-AL
Tvarové těsnění	NBR
O-kroužek	NBR
Krytí	IP 68 – 10 bar / IP 69K
Pracovní teplota	-20 °C – 70 °C



II 2G 1D



AG	\varnothing mm	GL mm	H mm	\varnothing mm	Obj. č.
PG 9	4–8	15	29	19	1.215.0901.14
PG 11	6–10	15	32,5	22	1.215.1101.14
PG 13,5	7–12	15	35,5	24	1.215.1301.14
PG 16	10–14	10	37,5	27	1.215.1601.14
PG 21	13–18	11	41	33	1.215.2101.14
PG 29	18–25	11	49	42	1.215.2901.14
PG 36	22–32	13	58	53	1.215.3601.14
PG 42	32–38	13	61,5	60	1.215.4201.14
PG 48	37–44	14	62	65	1.215.4801.14