

touch pen system ELO for capacitive or resistive touch screen ELO pen, including holder for 22.5 mm, screw on or glue on for capacitive and resistive touch screens more information, quantity and content: see technical specifications



Figure similar

General information	
Product type designation	universal touch pen system (resistive/capacitive), including support
Control elements	
Frame size/design	
<ul style="list-style-type: none"> <li>Standard</li> <li>Exceptional</li> <li>Ergonomic</li> </ul>	Yes; For industrial applications Yes; Spare caps can be stowed in the pen Yes; With holder
Installation type/mounting	
Mounting type	Wall-mounting bracket can be mounted with mounting disk, 2x M3 screw or adhesive pads
Mounting position	Horizontal
Front mounting	Yes; also optimized for PRO Extension Unit 22.5 mm opening (from HS01)
Wall mounting/direct mounting	Yes
Degree and class of protection	
IP (at the front)	IP65 (depending on mounting)
Standards, approvals, certificates	
RoHS conformity	Yes; Threaded insert screw tip - according to Article 33 of the REACH Regulation, we hereby inform you that the threaded insert supplied by us contains a substance included on the REACH Candidate List (SVHC). The substance in question is lead. CAS number: 7439-92-1 / EC number: 231-100-4
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	Yes; only suitable under certain conditions due to different environmental conditions; replacement cycle can be increased
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-40 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended 80 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-40 °C 80 °C
Relative humidity	
<ul style="list-style-type: none"> <li>Operation, max.</li> </ul>	95 %
Mechanics/material	
Material	

<ul style="list-style-type: none"> <li>• Plastic</li> <li>• Aluminum</li> </ul>	Yes; Attachment cord
Enclosure material (front)	Yes; pen, anodized
<ul style="list-style-type: none"> <li>• Plastic</li> </ul>	Yes; pen holder
Color	black, anodized
Enclosure color (front)	Black
<b>Dimensions</b>	
Length	150 mm
Diameter	14 mm
Enclosure diameter	37 mm; Diameter wall-mounting bracket
Mounting cutout, height	39 mm; Height wall-mounting bracket
<b>Weights</b>	
Weight without packaging	0.13 kg
Weight incl. packaging	0.14 kg
<b>Scope of supply</b>	
Delivery quantity in pieces	1; 1x touch pen, 1x attachment cord, 1x resistive/capacitive cap, 1x resistive cap (in the touch pen), 1x complete wall bracket
<b>Other</b>	
Merchandise	Yes; ELO touch pen, small
Manufacturer name	QUERUM products UG
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany
contacting the manufacturer	email: querumproducts@web.de
Target devices	For common capacitive and resistive touch systems
Note:	Length of the interconnecting lead 53 cm to 100 cm
<b>Usable in the following products</b>	
<ul style="list-style-type: none"> <li>• Product 21</li> </ul>	6AV2124-*

**last modified:**

5/31/2021 