



SIMATIC IOT2050; 1x M.2; 2x Gbit Ethernet RJ45; display port; 2x USB2.0; 16 GB eMMC; SD card slot; 24 V DC industrial power supply

General information	
Product type designation	IOT2050
Installation type/mounting	
Design	IoT Gateway, built-in unit
Supply voltage	
Type of supply voltage	12/24 V DC
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Processor	
Processor type	ARM TI AM6548 HS
Graphic	
Graphics controller	Integrated
Drives	
Slot for drives	1x microSD card slot
Memory	
Type of memory	DDR4
Main memory	2 GB RAM
Capacity of main memory, max.	2 Gbyte
Hardware configuration	
Slots	
• free slots	1x Arduino; 2x M.2 (B-key & E-Key)
Digital inputs	
Number of digital inputs	20
Input voltage	
• Type of input voltage	DC
Analog inputs	
Input ranges	
• Voltage	Yes; 0 ... 5 V
Interfaces	
Number of PROFINET interfaces	2
USB port	2x USB
Connection for keyboard/mouse	USB
serial interface version	1x COM (1x RS 232 / 422 / 485)
Multimedia	
• Audio In/Out	No
• Microphone In	No
Video interfaces	
• Graphics interface	1x DisplayPort
Industrial Ethernet	
• Industrial Ethernet interface	2x Ethernet (RJ45)

— 100 Mbps	Yes
— 1000 Mbps	Yes
Interrupts/diagnostics/status information	
LED status display	Yes
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
• Watchdog	Yes
EMC	
Interference immunity against discharge of static electricity	
• Interference immunity against discharge of static electricity	±4 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2
Interference immunity against high-frequency electromagnetic fields	
• Interference immunity against high frequency radiation	10 V/m for 80 ... 1 000 MHz, 80 % AM according to IEC 61000-4-3; 3 V/m for 1.4 ... 6 GHz, 80 % AM according to IEC 61000-4-3
Interference immunity to cable-borne interference	
• Interference immunity on supply cables	±2 kV (according to IEC 61000-4-4, burst); ±1 kV (according to IEC 61000-4-5, surge pulse/line to line); ±2 kV (according to IEC 61000-4-5, surge pulse/line to ground)
• Interference immunity on signal cables >30m	±2 kV acc. to IEC 61000-4-5, surge, length > 30 m
• Interference immunity on signal cables < 30m	±1 kV acc. to IEC 61000-4-4, Burst
Interference immunity against voltage surge	
• asymmetric interference	±2 kV acc. to IEC 61000-4-5, surge asymmetric
• symmetric interference	±1 kV acc. to IEC 61000-4-5, surge symmetric
Degree and class of protection	
IP degree of protection	IP20
IP (all-round)	IP20
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
FCC	Yes
EMC	CE, EN 61000-6-4:2007 +A1:2011, EN 61000-6-2:2005, CE, EN IEC 61000-6-4:2019, EN IEC 61000-6-2:2019
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	196 kg
— global warming potential, (during production) [CO2 eq]	18.7 kg
— global warming potential, (during operation) [CO2 eq]	179 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-2.28 kg
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Relative humidity	
• Relative humidity	5 ... 85 % at 30 °C, no condensation
• Operation, max.	85 %
Vibrations	
• Vibration resistance during operation acc. to IEC 60068-2-6	tested according to IEC 60068-2-6: 10 cycles; 5 to 8.4 Hz: deflection 3.5 mm; 8.4 to 200 Hz: acceleration 9.8 m/s²
Shock testing	

- Shock load during operation

Tested according to IEC 60068-2-27: 150 m/s², 11 ms

Operating systems

pre-installed operating system	SIMATIC Industrial OS
without operating system	No

Mechanics/material

Enclosure material (front)	plastic
• Plastic	Yes
• Aluminum	Yes
• Stainless steel	Yes
• Glass	No

Dimensions

Width	37 mm
Height	142 mm
Depth	100 mm

Classifications

	Version	Classification
eClass	14	19-20-01-02
eClass	12	19-20-01-02
eClass	9.1	19-20-01-02
eClass	9	19-20-01-02
eClass	8	19-20-01-02
eClass	7.1	19-20-01-02
eClass	6	19-20-01-02
ETIM	9	EC001413
ETIM	8	EC001413
ETIM	7	EC001413

Approvals / Certificates

General Product Approval	Dangerous goods	Environment
--------------------------	-----------------	-------------

[Manufacturer Declaration](#)

[Dangerous goods information](#)



last modified:

4/3/2025