


# HSK-K-PVDF

Item number 1299160014



## Technical data

|                       |                                                                   |
|-----------------------|-------------------------------------------------------------------|
| Material              | PVDF V0 according to UL94                                         |
| Seal                  | FKM                                                               |
| Protection class      | IP 54 , IP 68 with additional O-ring:IP68 - 10bar/30min , IP 69 K |
| Type Rating by        | 12 , 4 , 4X , 6 (with additional O-ring) , UL 50E                 |
| Temperature range     | -35°C to +150°C                                                   |
| Colour                | natural                                                           |
| Variant               | PG                                                                |
| External thread (AG)  | PG 16                                                             |
| Cable diameter        | 10 - 14 mm                                                        |
| Thread length (GL)    | 10 mm                                                             |
| Height (H)            | 28 mm                                                             |
| Wrench size (SW1/SW2) | 27/27 mm                                                          |
| Tightening torque     | 4.5 Nm                                                            |



# HSK-K-PVDF

Item number 1299160014

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 50            |
| EAN code              | 4033878418499 |
| Weight                | 0.01933 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 39269097      |

Note:

