


## Plug V-N-Ms (metric, PG)

Material	Nickel-plated brass
Protection class	IP 54


RoHS



AG	D mm	GL mm	H mm	Item-No
M12 x 1.5	14	5	7.5	1.052.1200.50
M16 x 1.5	18	5	8	1.052.1600.50
M20 x 1.5	22	6.5	9.5	1.052.2000.50
M25 x 1.5	28	7	11	1.052.2500.50
M32 x 1.5	35	8	12	1.052.3200.50
M40 x 1.5	45	8.1	13	1.052.4000.50
M50 x 1.5	54	9	15	1.052.5000.50
M63 x 1.5	67	10	16	1.052.6300.50
PG 7	14	5	8	1.052.0700.01
PG 9	17	6	9	1.052.0900.01
PG 11	20	6	9	1.052.1100.01
PG 13.5	22	6.5	9.5	1.052.1300.01
PG 16	24	6.5	9.5	1.052.1600.01
PG 21	30	7	11	1.052.2100.01
PG 29	39	8	12	1.052.2900.01
PG 36	50	9	15	1.052.3600.01
PG 42	57	10	16	1.052.4200.01
PG 48	64	10	16	1.052.4800.01

# Accessories

## Plug V-N-Ms-SD (metric, PG)



Material	Nickel-plated brass
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
Temperature range	-40°C to +80°C

RoHS

// Other O-Ring materials on request

AG	D mm	GL mm	H mm	Item-No
M12 x 1.5	14	6.5	9.5	1.052.1201.50
M16 x 1.5	20	6	9	1.052.1601.50
M20 x 1.5	24	6.5	9.5	1.052.2001.50
M25 x 1.5	28	7	11	1.052.2501.50
M32 x 1.5	35	8	12.5	1.052.3201.50
M40 x 1.5	45	8	12	1.052.4001.50
M50 x 1.5	55	9	15	1.052.5001.50
M63 x 1.5	68	10	16	1.052.6301.50
PG 7	14	4.8	8	1.052.0701.01
PG 9	17	5.5	9	1.052.0901.01
PG 11	20	5.5	9	1.052.1101.01
PG 13.5	22	6	9.5	1.052.1301.01
PG 16	24	6	9.5	1.052.1601.01
PG 21	30	6.5	11	1.052.2101.01
PG 29	39	7.5	12	1.052.2901.01
PG 36	50	9	15	1.052.3601.01
PG 42	57	10	16	1.052.4201.01
PG 48	64	10	16	1.052.4801.01