


Plug V-N-FS (metric, PG)



Material	Polyamide
Protection class	IP 54
Temperature range	-40°C to +100°C
Colour	grey / black
RAL	7035 / 9005

RoHS

AG	D mm	GL mm	H mm	Item-No grey	Item-No black
M12 x 1.5	15	6	10	1.251.1200.50	1.251.1201.50
M16 x 1.5	20	7	11	1.251.1600.50	
M16 x 1.5	20	7	11.5		1.251.1601.50
M20 x 1.5	25	6	9.5	1.251.2000.50	1.251.2001.50
M25 x 1.5	30	11	15.5	1.251.2500.50	1.251.2501.50
M32 x 1.5	38	11	16	1.251.3200.50	1.251.3201.50
M40 x 1.5	46	13	18	1.251.4000.50	1.251.4001.50
M50 x 1.5	56	13	18.5	1.251.5000.50	1.251.5001.50
M63 x 1.5	69	15	19	1.251.6300.50	1.251.6301.50
PG 7	15	6	8	1.251.0700.11	1.251.0701.11
PG 9	19	6	9	1.251.0900.11	1.251.0901.11
PG 11	22	6	9	1.251.1100.11	1.251.1101.11
PG 13.5	25	6	9.5	1.251.1300.11	1.251.1301.11
PG 16	27	6	9.5	1.251.1600.11	1.251.1601.11
PG 21	33	8	11	1.251.2100.11	1.251.2101.11
PG 29	44	8	12	1.251.2900.11	1.251.2901.11
PG 36	55	10	15	1.251.3600.11	1.251.3601.11
PG 42	62	10	16	1.251.4200.11	1.251.4201.11
PG 48	69	12	16	1.251.4800.11	1.251.4801.11