


Plug V-NE-Ms (metric, PG)



Material Nickel-plated brass

RoHS

Protection class IP 54

- // Without o-ring
- // NPT thread on request
- // Elongated threads on request

AG	GL mm	H mm	SW mm	Item-No
M12 x 1.5	6.5	9.5	14	1.155.1200.50
M16 x 1.5	6	9	19	1.155.1600.50
M20 x 1.5	6	9.5	22	1.155.2000.50
M25 x 1.5	7	10.5	30	1.155.2500.50
M32 x 1.5	8	12.5	41	1.155.3200.50
M40 x 1.5	8	13	46	1.155.4000.50
M50 x 1.5	9	15	55	1.155.5000.50
M63 x 1.5	10	16.5	70	1.155.6300.50
PG 7	5	8	14	1.155.0700.01
PG 9	6	9	17	1.155.0900.01
PG 11	6	9.5	20	1.155.1100.01
PG 13.5	6.5	10	22	1.155.1300.01
PG 16	6.5	10	24	1.155.1600.01
PG 21	7	10.5	30	1.155.2100.01
PG 29	8	12.5	41	1.155.2900.01
PG 36	8	13	50	1.155.3600.01
PG 42	9	15	58	1.155.4200.01
PG 48	10	16.5	65	1.155.4800.01

