


Accessories

Plug V-NE-Ms-SD (metric, PG)



Material	Nickel-plated brass
Material o-ring	NBR / FKM
Protection class	IP 68 – 10 bar / IP 69 K
Temperature range	-20°C to +95°C / -20°C to +180°C

RoHS

- // NPT thread on request
- // Elongated threads on request
- // Other O-Ring materials on request

AG	GL mm	H mm	SW mm	Item-No NBR	Item-No FKM
M12 x 1.5	6.5	9.5	14	1.156.1200.50	1.157.1200.50
M16 x 1.5	6	9	19	1.156.1600.50	1.157.1600.50
M20 x 1.5	6	9.5	22	1.156.2000.50	1.157.2000.50
M25 x 1.5	7	10.5	30	1.156.2500.50	1.157.2500.50
M32 x 1.5	8	12.5	41	1.156.3200.50	1.157.3200.50
M40 x 1.5	8	13	46	1.156.4000.50	1.157.4000.50
M50 x 1.5	9	15	55	1.156.5000.50	1.157.5000.50
M63 x 1.5	10	16.5	70	1.156.6300.50	1.157.6300.50
PG 7	5	8	14	1.156.0700.01	1.157.0700.01
PG 9	6	9	17	1.156.0900.01	1.157.0900.01
PG 11	6	9.5	20	1.156.1100.01	1.157.1100.01
PG 13.5	6.5	10	22	1.156.1300.01	1.157.1300.01
PG 16	6.5	10	24	1.156.1600.01	1.157.1600.01
PG 21	7	10.5	30	1.156.2100.01	1.157.2100.01
PG 29	8	12.5	41	1.156.2900.01	1.157.2900.01
PG 36	8	13	50	1.156.3600.01	1.157.3600.01
PG 42	9	15	58	1.156.4200.01	1.157.4200.01
PG 48	10	16.5	65	1.156.4800.01	1.157.4800.01

