


Ex Accessories

Plug V-Ex (metric, PG)



Material	Polyamide, fiber reinforced
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperature range	-20°C to +90°C
Colour	black
RAL	9005

RoHS

AG	D mm	GL mm	H mm	SW mm	⊙	Item-No
M12 x 1.5	16.5	8.5	13	15	6	1.297.1201.50
M16 x 1.5	20.5	8.5	13	19	8	1.297.1601.50
M20 x 1.5	25.5	9	14.5	24	8	1.297.2001.50
M25 x 1.5	30.5	10.5	16	28	8	1.297.2501.50
M32 x 1.5	38	11.5	17.5	36	8	1.297.3201.50
M40 x 1.5	48	11.5	18	46	8	1.297.4001.50
M50 x 1.5	60	13.5	20	55	8	1.297.5001.50
M63 x 1.5	75	14.5	21	70	8	1.297.6301.50
PG 7	16.5	8.5	13	15	6	1.297.0701.11
PG 9	20.5	8.5	13	19	8	1.297.0901.11
PG 11	25.5	9	14.5	24	8	1.297.1101.11
PG 13.5	25.5	9	14.5	24	8	1.297.1301.11
PG 16	30.5	10.5	16	28	8	1.297.1601.11
PG 21	38	11.5	17.5	36	8	1.297.2101.11
PG 29	48	11.5	18	46	8	1.297.2901.11
PG 36	60	13.5	20	55	8	1.297.3601.11
PG 42	65	13.5	20	60	8	1.297.4201.11
PG 48	75	14.5	21	70	8	1.297.4801.11



to the assembly
instruction

