


Adapter RSD-Ms (metric, PG)



Material Nickel-plated brass

RoHS

Material o-ring NBR

Temperature range -40°C to +100°C

// O-ring made of FKM / VMQ on request

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1.5	M12 x 1.5	5	8	17	1.077.1612.50
M20 x 1.5	M12 x 1.5	6	9	22	1.077.2012.50
M20 x 1.5	M16 x 1.5	6	9	22	1.077.2016.50
M25 x 1.5	M16 x 1.5	7	10	27	1.077.2516.50
M25 x 1.5	M20 x 1.5	7	10	27	1.077.2520.50
M32 x 1.5	M16 x 1.5	8	11	34	1.077.3216.50
M32 x 1.5	M20 x 1.5	8	11	35	1.077.3220.50
M32 x 1.5	M25 x 1.5	8	11	34	1.077.3225.50
M40 x 1.5	M20 x 1.5	8	12	43	1.077.4020.50
M40 x 1.5	M25 x 1.5	8	12	43	1.077.4025.50
M40 x 1.5	M32 x 1.5	8	12	43	1.077.4032.50
M50 x 1.5	M25 x 1.5	9	13	55	1.077.5025.50
M50 x 1.5	M32 x 1.5	9	13	55	1.077.5032.50
M50 x 1.5	M40 x 1.5	9	13	55	1.077.5040.50
M63 x 1.5	M32 x 1.5	10	14	65	1.077.6332.50
M63 x 1.5	M40 x 1.5	10	14	65	1.077.6340.50
M63 x 1.5	M50 x 1.5	10	14	65	1.077.6350.50
PG 9	PG 7	6	8.8	17	1.077.0907.01
PG 11	PG 7	6	9	20	1.077.1107.01
PG 11	PG 9	6	9	20	1.077.1109.01
PG 13.5	PG 9	6.5	9.5	22	1.077.1309.01
PG 13.5	PG 11	6.5	9.5	22	1.077.1311.01
PG 16	PG 9	6.5	9.5	24	1.077.1609.01
PG 16	PG 11	6.5	9.5	24	1.077.1611.01
PG 16	PG 13.5	6.5	9.5	24	1.077.1613.01
PG 21	PG 11	7	10.3	30	1.077.2111.01
PG 21	PG 13.5	7	10.3	30	1.077.2113.01
PG 21	PG 16	7	10.3	30	1.077.2116.01
PG 29	PG 16	8	11.5	40	1.077.2916.01
PG 29	PG 21	8	11.5	40	1.077.2921.01
PG 36	PG 21	9	12.5	50	1.077.3621.01
PG 36	PG 29	9	12.5	50	1.077.3629.01
PG 42	PG 29	10	13.5	57	1.077.4229.01
PG 42	PG 36	10	13.5	57	1.077.4236.01
PG 48	PG 36	10	13.5	64	1.077.4836.01
PG 48	PG 42	10	13.5	64	1.077.4842.01

