


Adapter RSD-INOX (metric, PG)



Material	INOX 1.4305
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
Temperature range	-20°C to +95°C

RoHS

// Other O-Ring materials on request

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1.5	M12 x 1.5	6	9	19	1.097.1612.50
M20 x 1.5	M12 x 1.5	6	9.5	22	1.097.2012.50
M20 x 1.5	M16 x 1.5	6	9.5	22	1.097.2016.50
M25 x 1.5	M16 x 1.5	7	10.5	30	1.097.2516.50
M25 x 1.5	M20 x 1.5	7	10.5	30	1.097.2520.50
M32 x 1.5	M16 x 1.5	8	12.5	41	1.097.3216.50
M32 x 1.5	M20 x 1.5	8	12.5	41	1.097.3220.50
M32 x 1.5	M25 x 1.5	8	12.5	41	1.097.3225.50
M40 x 1.5	M20 x 1.5	8	13	46	1.097.4020.50
M40 x 1.5	M25 x 1.5	8	13	46	1.097.4025.50
M40 x 1.5	M32 x 1.5	8	13	46	1.097.4032.50
M50 x 1.5	M25 x 1.5	9	15	55	1.097.5025.50
M50 x 1.5	M32 x 1.5	9	15	55	1.097.5032.50
M50 x 1.5	M40 x 1.5	9	15	55	1.097.5040.50
M63 x 1.5	M32 x 1.5	10	16.5	65	1.097.6332.50
M63 x 1.5	M40 x 1.5	10	16.5	65	1.097.6340.50
M63 x 1.5	M50 x 1.5	10	16.5	65	1.097.6350.50
PG 9	PG 7	6	8.8	17	1.097.0907.01
PG 11	PG 7	6	9	22	1.097.1107.01
PG 11	PG 9	6	9	22	1.097.1109.01
PG 13.5	PG 9	6.5	9.5	22	1.097.1309.01
PG 13.5	PG 11	6.5	9.5	22	1.097.1311.01
PG 16	PG 9	6.5	9.5	24	1.097.1609.01
PG 16	PG 11	6.5	9.5	24	1.097.1611.01
PG 16	PG 13.5	6.5	9.5	24	1.097.1613.01
PG 21	PG 11	7	10.3	30	1.097.2111.01
PG 21	PG 13.5	7	10.3	30	1.097.2113.01
PG 21	PG 16	7	10.3	30	1.097.2116.01
PG 29	PG 16	8	11.5	41	1.097.2916.01
PG 29	PG 21	8	11.5	41	1.097.2921.01
PG 36	PG 21	9	12.5	50	1.097.3621.01
PG 36	PG 29	9	12.5	50	1.097.3629.01
PG 42	PG 29	10	13.5	60	1.097.4229.01
PG 42	PG 36	10	13.5	60	1.097.4236.01
PG 48	PG 36	10	13.5	65	1.097.4836.01
PG 48	PG 42	10	13.5	65	1.097.4842.01

