

Material	INOX 1.4305
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperature range	-20°C to +95°C

RoHS

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1.5	M12 x 1.5	5	15	19	1.098.1612.50
M20 x 1.5	M12 x 1.5	6	15.5	22	1.098.2012.50
M20 x 1.5	M16 x 1.5	6	15.5	22	1.098.2016.50
M25 x 1.5	M16 x 1.5	7	15.5	30	1.098.2516.50
M25 x 1.5	M20 x 1.5	7	15.5	30	1.098.2520.50
M32 x 1.5	M16 x 1.5	8	16.5	41	1.098.3216.50
M32 x 1.5	M20 x 1.5	8	12.5	41	1.098.3220.50
M32 x 1.5	M25 x 1.5	8	12.5	41	1.098.3225.50
M40 x 1.5	M20 x 1.5	8	17	46	1.098.4020.50
M40 x 1.5	M25 x 1.5	8	17	46	1.098.4025.50
M40 x 1.5	M32 x 1.5	8	17	46	1.098.4032.50
M50 x 1.5	M25 x 1.5	9	13.5	55	1.098.5025.50
M50 x 1.5	M32 x 1.5	9	13.5	55	1.098.5032.50
M50 x 1.5	M40 x 1.5	9	13.5	55	1.098.5040.50
M63 x 1.5	M32 x 1.5	10	16.5	65	1.098.6332.50
M63 x 1.5	M40 x 1.5	10	16.5	65	1.098.6340.50
M63 x 1.5	M50 x 1.5	10	16.5	65	1.098.6350.50
PG 9	PG 7	6	8.8	17	1.098.0907.01
PG 11	PG 7	6	9	20	1.098.1107.01
PG 11	PG 9	6	9	20	1.098.1109.01
PG 13.5	PG 9	6.5	9.5	22	1.098.1309.01
PG 13.5	PG 11	6.5	9.5	22	1.098.1311.01
PG 16	PG 9	6.5	9.5	24	1.098.1609.01
PG 16	PG 11	6.5	9.5	24	1.098.1611.01
PG 16	PG 13.5	6.5	9.5	24	1.098.1613.01
PG 21	PG 11	7	10.3	30	1.098.2111.01
PG 21	PG 13.5	7	10.3	30	1.098.2113.01
PG 21	PG 16	7	10.3	30	1.098.2116.01
PG 29	PG 16	8	11.5	40	1.098.2916.01
PG 29	PG 21	8	11.5	40	1.098.2921.01
PG 36	PG 21	9	12.5	50	1.098.3621.01
PG 36	PG 29	9	12.5	50	1.098.3629.01
PG 42	PG 29	10	13.5	57	1.098.4229.01
PG 42	PG 36	10	13.5	57	1.098.4236.01
PG 48	PG 36	10	13.5	64	1.098.4836.01
PG 48	PG 42	10	13.5	64	1.098.4842.01




to the assembly
instruction



Ex Accessories

Plug RSD-INOX-VMQ-Ex (metric, PG)



Material	INOX 1.4305
Material o-ring	VMQ (silicone)
Protection class	IP 68 – 10 bar / IP 69 K
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperature range	-60°C to +180°C

RoHS

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1.5	M12 x 1.5	5	9	19	1.099.1612.50
M20 x 1.5	M12 x 1.5	6	9.5	22	1.099.2012.50
M20 x 1.5	M16 x 1.5	6	9.5	22	1.099.2016.50
M25 x 1.5	M16 x 1.5	7	10.5	30	1.099.2516.50
M25 x 1.5	M20 x 1.5	7	10.5	30	1.099.2520.50
M32 x 1.5	M16 x 1.5	8	12.5	41	1.099.3216.50
M32 x 1.5	M20 x 1.5	8	12.5	41	1.099.3220.50
M32 x 1.5	M25 x 1.5	8	12.5	41	1.099.3225.50
M40 x 1.5	M20 x 1.5	8	13	46	1.099.4020.50
M40 x 1.5	M25 x 1.5	8	13	46	1.099.4025.50
M40 x 1.5	M32 x 1.5	8	13	46	1.099.4032.50
M50 x 1.5	M25 x 1.5	9	13.5	55	1.099.5025.50
M50 x 1.5	M32 x 1.5	9	13.5	55	1.099.5032.50
M50 x 1.5	M40 x 1.5	9	13.5	55	1.099.5040.50
M63 x 1.5	M32 x 1.5	10	16.5	65	1.099.6332.50
M63 x 1.5	M40 x 1.5	10	16.5	65	1.099.6340.50
M63 x 1.5	M50 x 1.5	10	16.5	65	1.099.6350.50
PG 9	PG 7	6	8.8	17	1.099.0907.01
PG 11	PG 7	6	9	20	1.099.1107.01
PG 11	PG 9	6	9	20	1.099.1109.01
PG 13.5	PG 9	6.5	9.5	22	1.099.1309.01
PG 13.5	PG 11	6.5	9.5	22	1.099.1311.01
PG 16	PG 9	6.5	9.5	24	1.099.1609.01
PG 16	PG 11	6.5	9.5	24	1.099.1611.01
PG 16	PG 13.5	6.5	9.5	24	1.099.1613.01
PG 21	PG 11	7	10.3	30	1.099.2111.01
PG 21	PG 13.5	7	10.3	30	1.099.2113.01
PG 21	PG 16	7	10.3	30	1.099.2116.01
PG 29	PG 16	8	11.5	40	1.099.2916.01
PG 29	PG 21	8	11.5	40	1.099.2921.01
PG 36	PG 21	9	12.5	50	1.099.3621.01
PG 36	PG 29	9	12.5	50	1.099.3629.01
PG 42	PG 29	10	13.5	57	1.099.4229.01
PG 42	PG 36	10	13.5	57	1.099.4236.01
PG 48	PG 36	10	13.5	64	1.099.4836.01
PG 48	PG 42	10	13.5	64	1.099.4842.01



to the assembly
instruction

