


Adapter E-M-PA type A (metric, PG)




Material	Polyamide
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS

// For further sizes see type C

AG	IG	Type	d mm	GL mm	H mm	SW mm	Item-No
M12 x 1.5	PG 7	A	6.5	8	12	17	1.239.1207.50
M12 x 1.5	M16 x 1.5	A	6.5	8	12	21	1.239.1216.50
M16 x 1.5	M20 x 1.5	A	9	8	13	25	1.239.1620.50
M20 x 1.5	PG 13.5	A	14	8	13	25	1.239.2013.50
M20 x 1.5	M25 x 1.5	A	14	8	15	30	1.239.2025.50
PG 9	M16 x 1.5	A	9	8	12	21	1.239.0916.11
PG 13.5	M20 x 1.5	A	14	8	13	25	1.239.1320.11
PG 16	M25 x 1.5	A	16	8	15	30	1.239.1625.11
PG 21	M32 x 1.5	A	21	8	15	37	1.239.2132.11
PG 29	M40 x 1.5	A	30	10	17	45	1.239.2940.11

Adapter E-M-PA type C (metric, PG)



Material	Polypropylene
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS

// For further sizes see type A

AG	IG	Type	d mm	GL mm	H mm	Item-No
M16 x 1.5	PG 9	C	8.5	1	19	1.239.1609.50
M25 x 1.5	M32 x 1.5	C	16.5	15	15	1.239.2532.50
M32 x 1.5	M40 x 1.5	C	23	15	19.5	1.239.3240.50
M40 x 1.5	M50 x 1.5	C	30	15	19.5	1.239.4050.50
M50 x 1.5	M63 x 1.5	C	39	15	20	1.239.5063.50
M63 x 1.5	PG 48	C	51	15	20	1.239.6348.50
PG 7	M12 x 1.5	C	6	15	19	1.239.0712.11
PG 11	M20 x 1.5	C	11.5	15	19	1.239.1120.11
PG 36	M50 x 1.5	C	37	15	19.5	1.239.3650.11
PG 42	M50 x 1.5	C	43	15	19.5	1.239.4250.11
PG 48	M63 x 1.5	C	48	15	20	1.239.4863.11