


Adapter RSD-MS-Ex d (metric)



Material	Nickel-plated brass
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
Ex-protection level	II 2G Ex db eb IIC Gb / II 1D Ex ta IIIC Da
Temperature range	-20°C to +95°C

RoHS

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1.5	M12 x 1.5	16	19	19	1.878.1612.50
M20 x 1.5	M12 x 1.5	16	19.5	22	1.878.2012.50
M20 x 1.5	M16 x 1.5	16	19.5	22	1.878.2016.50
M25 x 1.5	M16 x 1.5	16	19.5	30	1.878.2516.50
M25 x 1.5	M20 x 1.5	16	19.5	30	1.878.2520.50
M32 x 1.5	M16 x 1.5	16	20.5	41	1.878.3216.50
M32 x 1.5	M20 x 1.5	16	20.5	41	1.878.3220.50
M32 x 1.5	M25 x 1.5	16	20.5	41	1.878.3225.50
M40 x 1.5	M20 x 1.5	16	21	46	1.878.4020.50
M40 x 1.5	M25 x 1.5	16	21	46	1.878.4025.50
M40 x 1.5	M32 x 1.5	16	21	46	1.878.4032.50
M50 x 1.5	M25 x 1.5	16	21	55	1.878.5025.50
M50 x 1.5	M32 x 1.5	16	21	55	1.878.5032.50



to the assembly
instruction

