


Ex cable glands

HSK-MZ-Ex d (metric, NPT)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL 94
Seal	FKM
Material o-ring	FKM
Protection class	IP 68 – 10 bar / IP 69 K
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperature range	-60°C to +105°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1.5	3 – 6.5	16	26	14/14	7.5	1.628.1200.50
M16 x 1.5	5 – 10	16	30.2	20/20	9	1.628.1600.50
M20 x 1.5	10 – 14	16	34	24/24	10	1.628.2000.50
M25 x 1.5	13 – 18	16	37.8	30/30	12	1.628.2500.50
M32 x 1.5	18 – 25	16	44	40/40	15	1.628.3200.50
M40 x 1.5	22 – 32	16	51.5	50/50	24	1.628.4000.50
NPT 3/8"	5 – 10	16	30	20/20	9	1.628.3800.70
NPT 1/2"	10 – 14	20	33.6	24/24	10	1.628.1200.70
NPT 3/4"	13 – 18	20.5	37.8	30/30	12	1.628.3400.70
NPT 1"	18 – 25	25	44	40/40	15	1.628.1000.70
NPT 1 1/4"	22 – 32	25	51.5	50/50	24	1.628.5400.70
NPT 1 1/2"	22 – 32	26.5	51.5	50/50	24	1.628.6400.70



to the assembly
instruction

