


# HSK-W

Item number 1313200050



## Technical data

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Material             | Polyamide                                         |
| Seal                 | NBR                                               |
| Material o-ring      | NBR                                               |
| Protection class     | IP 68 - 1bar/30min                                |
| Temperature range    | -40°C to +100°C                                   |
| Colour               | grey                                              |
| RAL                  | 7035                                              |
| Variant              | Metric                                            |
| External thread (AG) | M20 x 1,5                                         |
| Cable diameter       | 6 - 12 mm                                         |
| Thread length (GL)   | 9 mm                                              |
| Height (H)           | 30.5 mm                                           |
| Length (L)           | 57 mm                                             |
| Wrench size (SW)     | 24 mm                                             |
| Tightening torque    | 4 Nm                                              |
| Type Rating by       | 12 , 4 , 4X , 6 (with additional O-ring) , UL 50E |



# HSK-W

Item number 1313200050

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 25            |
| EAN code              | 4033878419687 |
| Weight                | 0.032 kg      |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 39269097      |

Note:



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)