



*** spare part *** SIMATIC ET 200MP. PROFINET IO device interface module IM 155-5 PN HF, for ET 200MP electronic modules; up to 12 IO modules without PS; up to 30 IO modules with additional PS; integrated 2-port switch; RJ45 shared device; MRP; IRT ≥ 0.25 ms; isochronous mode firmware update; I&M0...3; prioritized startup, S2 redundancy; shared device with 4 controllers suitable for operation with the active backplane bus (FW V4.4 or higher)

General information	
Product type designation	IM 155-5 PN HF
HW functional status	From FS03
Firmware version	V4.4
<ul style="list-style-type: none"> FW update possible 	Yes
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0X0312
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Module swapping during operation (hot swapping) 	Yes; In combination with active backplane bus
<ul style="list-style-type: none"> Isochronous mode 	Yes
<ul style="list-style-type: none"> IRT 	Yes
<ul style="list-style-type: none"> Tool changer 	No
<ul style="list-style-type: none"> Local coupling, IO data 	No
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	V16
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	use GSD file
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	GSDML V2.3
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	5 ms
Input current	
Current consumption (rated value)	0.2 A; at 24 V DC and without load
Current consumption, max.	1.2 A
Inrush current, max.	9 A
I^2t	0.09 A ² ·s
Power	
Infeed power to the backplane bus	14 W
Power consumption from the backplane bus	2.3 W; in case of operation with separate system power supply to the left of IM
Power loss	
Power loss, typ.	4.5 W
Address area	

Address space per module	
• Address space per module, max.	256 byte; For input and output data respectively
Address space per station	
• Address space per station, max.	512 byte; For input and output data respectively
Hardware configuration	
Integrated power supply	Yes; 14 W
System power supply can be plugged in to left of IM	Yes; only with design with U-connectors
Number of permissible power segments	3; incl. interface module
Rack	
• Modules per rack, max.	30; I/O modules
Submodules	
• Number of submodules per station, max.	256; 9 per I/O module
Interfaces	
Number of PROFINET interfaces	1; 2 ports (switch)
1. Interface	
Interface types	
• RJ 45 (Ethernet)	Yes
• Number of ports	2
• integrated switch	Yes
• BusAdapter (PROFINET)	No
Protocols	
• PROFINET IO Device	Yes
• Open IE communication	Yes
• Media redundancy	Yes; PROFINET MRP client / HRP client
PROFINET IO Device	
Services	
— IRT	Yes; 250 µs to 4 ms in 125 µs frame
— PROFIenergy	No
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	4
Interface types	
RJ 45 (Ethernet)	
• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• 100 Mbps	Yes
• Autonegotiation	Yes
• Autocrossing	Yes
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	Yes
PROFIBUS	No
EtherNet/IP	No
Modbus TCP	No
Redundancy mode	
• PROFINET system redundancy (S2)	Yes; NAP S2
— on S7-1500R/H	Yes
— on S7-400H	Yes; use GSD file
• PROFINET system redundancy (R1)	No
• H-Sync forwarding	Yes
Media redundancy	
— MRP	Yes
— MRPD	Yes
Open IE communication	
• TCP/IP	Yes
• SNMP	Yes
• LLDP	Yes
Isochronous mode	
Equidistance	Yes
shortest clock pulse	250 µs

max. cycle	4 ms	
Bus cycle time (TDP), min.	250 µs	
Jitter, max.	1 µs	
Interrupts/diagnostics/status information		
Status indicator	Yes	
Alarms	Yes	
Diagnostics function	Yes	
Diagnostics indication LED		
• RUN LED	Yes; green LED	
• ERROR LED	Yes; red LED	
• MAINT LED	Yes; Yellow LED	
• Connection display LINK TX/RX	Yes; 2x green-yellow LEDs	
Potential separation		
between backplane bus and electronics	No	
between PROFINET and all other circuits	Yes; 1500 V AC (type test)	
between supply and all other circuits	No	
Permissible potential difference		
between different circuits	Safety extra low voltage SELV	
Isolation		
Isolation tested with	707 V DC (type test)	
Ambient conditions		
Ambient temperature during operation		
• horizontal installation, min.	-25 °C; from FS04	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-25 °C; from FS04	
• vertical installation, max.	40 °C	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual	
Absolute humidity		
• dew point, min.	-60 °C; suitable for dry room applications	
Connection method		
ET-Connection		
• via BU/BA Send	No	
Dimensions		
Width	35 mm	
Height	147 mm	
Depth	129 mm	
Weights		
Weight, approx.	350 g	
Classifications		
	Version	Classification
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05
Approvals / Certificates		
General Product Approval		



[Manufacturer Declaration](#)

[Miscellaneous](#)

[China RoHS](#)



General Product Approval

For use in hazardous locations



[EM](#)



[EM](#)

[CCC-Ex](#)

For use in hazardous locations

Maritime application



[Type Examination Certificate](#)



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

Industrial Communication

[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

[PROFINET](#)

last modified:

2/4/2026