


# HSK-INOX-PVDF-Ex-d

Item number 1633120071



## Technical data

|                              |  |
|------------------------------|--|
| <b>Material</b>              | INOX 1.4404                              |
| <b>Clamping insert</b>       | PVDF                                     |
| <b>Seal</b>                  | FKM                                      |
| <b>Material o-ring</b>       | FKM                                      |
| <b>Protection class</b>      | IP68 - 10bar/30min , IP 69 K             |
| <b>Ex-protection level</b>   | II 1D Ex ta IIIC Da , II 2G Ex db IIC Gb |
| <b>Temperature range</b>     | -20°C to +130°C                          |
| <b>Variant</b>               | NPT                                      |
| <b>External thread (AG)</b>  | NPT 1/2"                                 |
| <b>Cable diameter</b>        | 7 - 12 mm                                |
| <b>Thread length (GL)</b>    | 20 mm                                    |
| <b>Height (H)</b>            | 25 mm                                    |
| <b>Wrench size (SW1/SW2)</b> | 24/24 mm                                 |
| <b>Tightening torque</b>     | 10 Nm                                    |

# HSK-INOX-PVDF-Ex-d

Item number 1633120071

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 25            |
| EAN code              | 4033878434437 |
| Weight                | 0.04803 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-34   |
| Customs tariff number | 73269098      |

Note:

