



Materiál poniklovaná mosaz  
 Vložka PA  
 Tvarové těsnění NBR  
 O-kroužek NBR  
 Krytí IP 68 – 10 / IP 69K barů  
 v uvedeném rozsahu sevření  
 Pracovní teplota -40 °C – 100 °C



AG	$\varnothing$ mm	GL mm	H mm	 mm	Obj. č
M 12 x 1,5	3 - 6,5	6,5	19	14	1.609.1200.50
M 12 x 1,5	2 - 5	6,5	19	14	1.609.1200.51
M 16 x 1,5	4 - 8	6	21	17 / 19	1.609.1600.50
M 16 x 1,5	2 - 6	6	21	17 / 19	1.609.1600.51
M 16 x 1,5	5 - 10	6	22	20	1.609.1611.50
M 20 x 1,5	6 - 12	6	23	22	1.609.2000.50
M 20 x 1,5	5 - 9	6	23	22	1.609.2000.51
M 20 x 1,5	10 - 14	6	24	24	1.609.2016.50
M 25 x 1,5	13 - 18	7	26	30	1.609.2500.50
M 25 x 1,5	9 - 16	7	26	30	1.609.2500.51
M 32 x 1,5	18 - 25	8	31	40	1.609.3200.50
M 32 x 1,5	13 - 20	8	31	40	1.609.3200.51
M 40 x 1,5	22 - 32	8	37	50	1.609.4000.50
M 40 x 1,5	20 - 26	8	37	50	1.609.4000.51
M 50 x 1,5	32 - 38	9	37	57	1.609.5000.50
M 50 x 1,5	25 - 31	9	37	57	1.609.5000.51
M 63 x 1,5	37 - 44	10	38	64 / 68	1.609.6300.50
M 63 x 1,5	29 - 35	10	38	64 / 68	1.609.6300.51

