

product type designation

Reader RF1070R OEM USB/RS232

SIMATIC RF1000 Access control reader RF1070R OEM variant ISO 14443 A/B Mifare, ISO15693 Legic Prime, Legic Advant USB port RS232 interface IP65 front, -25 to +55 °C 90x62x25 mm LxWxH with integrated antenna including 1.8 m USB cable company logo enclosed.



product brand name

SIMATIC RF

Technical Product Detail Page

<https://l.siemens.com/1P6GT2831-6BA60-0AX0>

suitability for operation

Legic, ISO 15693 and ISO 14443 A/B transponder, for connecting to PC and control systems, for front panels with customer-specific design

radio frequencies

operating frequency / rated value

13.56 MHz

range / maximum

0.03 m; Range is dependent on transponder type: observe <http://support.automation.siemens.com/WW/view/en/67384964>

protocol / with radio transmission

Legic Prime, Legic Advant, ISO 15693, ISO 14443 A/B, chip set: SM4200M, Felica, NXP NTAG21x, HID iClass

transfer rate / with radio transmission / maximum

106 kbit/s

product feature / multitag-capable

Yes

operating frequency / 1

2.4 GHz (only for BLE support)

electrical data

transfer rate / at the point-to-point connection / serial / maximum

115.2 kbit/s

interfaces

standard for interfaces / for communication

USB 2.0, RS232

type of electrical connection

1.8 m connecting cable with USB 2.0 type A connector or RS232 connecting cable

mechanical data

material

PC-GF

color

titanium gray

mounting distance / relating to metal surfaces / recommended / minimum

0 mm

supply voltage, current consumption, power loss

supply voltage / at DC

• rated value

5 V

•

4.6 ... 5.25 V

consumed current / at DC

• at 5 V / typical

0.15 A

• at 5 V / maximum

0.3 A

ambient conditions

ambient temperature

• during operation

-25 ... +55 °C

• during storage

-25 ... +55 °C

• during transport

-25 ... +55 °C

protection class IP

IP65; on front after professional gluing of the included front label and cabinet installation, IP20 rear

shock resistance

EN 60721-3-7 Class 7 M2

shock acceleration	300 m/s ²
vibrational acceleration	50 m/s ²
design, dimensions and weights	
width	90 mm
height	62 mm
depth	23.5 mm
net weight	0.12 kg
fastening method	4 M4 screws for cabinet installation
product features, product functions, product components / general	
display version	3-color LED
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus
certificate of suitability • IECEx	No
accessories	
accessories	Card holder, USB cable 0.5 m, RS232 connection cable, front label in customer design to be created by the customer, HID license card, BLE license card, cleanroom cover, desktop housing
further information / internet links	
internet link • to web page: selection aid TIA Selection Tool • to web page: RFID country approval • to web page: identification and localization systems • to web page: SiePortal • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support	https://www.siemens.com/tstcloud https://www.siemens.com/rfid-approvals https://www.siemens.com/ident https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)

Approvals / Certificates

General Product Approval



General Product Approval	Radio Equipment Type Approval Certificate
--------------------------	---

[Manufacturer Declaration](#)

[Industry Canada \(IC\)](#)

[Miscellaneous](#)

[Miscellaneous](#)

[FCC](#)

[Miscellaneous](#)

[Miscellaneous](#)

last modified:

6/28/2026 