



SIMATIC S7-1200, CPU 1215C, COMPACT CPU, DC/DC/RELAY, 2 PROFINET PORT, ONBOARD I/O: 14 DI 24V DC; 10 DO RELAY 2A, 2 AI 0-10V DC, 2 AO 0-20MA DC, POWER SUPPLY: DC 20.4 - 28.8 V DC, PROGRAM/DATA MEMORY: 125 KB

General information

Firmware version	V4.1
Engineering with	
• Programming package	STEP 7 V13 SP1 or higher

Supply voltage

Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	5 V
• permissible range, upper limit (DC)	250 V

Input current

Current consumption (rated value)	500 mA; CPU only
Current consumption, max.	1 500 mA; CPU with all expansion modules
Inrush current, max.	12 A; at 28.8 V DC

Encoder supply

24 V encoder supply	
• 24 V	L+ minus 4 V DC min.

Power losses

Power loss, typ.	12 W
------------------	------

Memory

Work memory	
• Integrated	125 kbyte
• expandable	No
Load memory	
• Integrated	4 Mbyte
• Plug-in (SIMATIC Memory Card), max.	with SIMATIC memory card
Backup	
• present	Yes; maintenance-free
• without battery	Yes
CPU processing times	
for bit operations, typ.	0.085 µs; / instruction
for word operations, typ.	1.7 µs; / instruction
for floating point arithmetic, typ.	2.3 µs; / instruction
CPU-blocks	
Number of blocks (total)	DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used
OB	
• Number, max.	Limited only by RAM for code
Data areas and their retentivity	
retentive data area in total (incl. times, counters, flags), max.	10 kbyte
Flag	
• Number, max.	8 kbyte; Size of bit memory address area
Local data	
• per priority class, max.	16 kbyte
Process image	
• Inputs, adjustable	1 kbyte
• Outputs, adjustable	1 kbyte
Hardware configuration	
Number of modules per system, max.	3 comm. modules, 1 signal board, 8 signal modules
Time of day	
Clock	
• Hardware clock (real-time clock)	Yes
• Deviation per day, max.	+/- 60 s/month at 25 °C
• Backup time	480 h; Typical
Digital inputs	
Number of digital inputs	14; Integrated
• of which, inputs usable for technological functions	6; HSC (High Speed Counting)
integrated channels (DI)	14

m/p-reading	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	14
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	5 V DC at 1 mA
• for signal "1"	15 VDC at 2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— Parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— Parameterizable	Yes
for counter/technological functions	
— Parameterizable	Yes; Single phase : 3 at 100 kHz & 3 at 30 kHz, differential: 3 at 80 kHz & 3 at 30 kHz
Cable length	
• shielded, max.	500 m; 50 m for technological functions
• Unshielded, max.	300 m; For technological functions: No
Digital outputs	
Number of digital outputs	10; Relays
integrated channels (DO)	10
Switching capacity of the outputs	
• with resistive load, max.	2 A
• on lamp load, max.	30 W with DC, 200 W with AC
Output delay with resistive load	
• "0" to "1", max.	10 ms; max.
• "1" to "0", max.	10 ms; max.
Switching frequency	
• of the pulse outputs, with resistive load, max.	1 Hz
Relay outputs	
• Number of relay outputs	10
• Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100,000
Cable length	
• shielded, max.	500 m
• Unshielded, max.	150 m
Analog inputs	
Number of analog inputs	2
Integrated channels (AI)	2; 0 to 10V

Input ranges	
• Voltage	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	≥100k ohms
Cable length	
• shielded, max.	100 m; twisted and shielded
Analog outputs	
Number of analog outputs	2
Integrated channels (AO)	2; 0 to 20 mA
Output ranges, current	
• 0 to 20 mA	Yes
Analog value creation	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	10 bit
• Integration time, parameterizable	Yes
• Conversion time (per channel)	625 μs
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
1st interface	
Interface type	PROFINET
Physics	Ethernet
Isolated	Yes
Automatic detection of transmission speed	Yes
Autonegotiation	Yes
Autocrossing	Yes
Functionality	
• PROFINET IO Device	Yes; Also simultaneously with IO-Device functionality
• PROFINET IO Controller	Yes
PROFINET IO Controller	
• Transmission rate, max.	100 Mbit/s
• Number of connectable IO devices, max.	16
PROFINET IO Device	
Services	
— Shared device	Yes
— Number of IO controllers with shared device, max.	2
Communication functions	
S7 communication	

• supported	Yes
• as server	Yes
• As client	Yes
Open IE communication	
• TCP/IP	Yes
• ISO-on-TCP (RFC1006)	Yes
• UDP	Yes
Web server	
• supported	Yes
• User-defined websites	Yes
Number of connections	
• overall	16; dynamically
Test commissioning functions	
Status/control	
• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
Forcing	
• Forcing	Yes
Diagnostic buffer	
• present	Yes
Traces	
• Number of configurable Traces	2; Up to 512 KB of data per trace are possible
Integrated Functions	
Number of counters	6
Counter frequency (counter) max.	100 kHz
Frequency meter	Yes
controlled positioning	Yes
Number of position-controlled positioning axes, max.	8
PID controller	Yes
Number of alarm inputs	4
Potential separation	
Galvanic isolation digital inputs	
• Potential separation digital inputs	500V AC for 1 minute
• between the channels, in groups of	1
Potential separation digital outputs	
• Potential separation digital outputs	Relays
• between the channels	No
• between the channels, in groups of	2
EMC	
Interference immunity against discharge of static electricity	

<ul style="list-style-type: none"> • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 	Yes
<ul style="list-style-type: none"> — Test voltage at air discharge 	8 kV
<ul style="list-style-type: none"> — Test voltage at contact discharge 	6 kV
Interference immunity to cable-borne interference	
<ul style="list-style-type: none"> • Interference immunity on supply lines acc. to IEC 61000-4-4 	Yes
<ul style="list-style-type: none"> • Interference immunity on signal lines acc. to IEC 61000-4-4 	Yes
Surge immunity	
<ul style="list-style-type: none"> • on the supply lines acc. to IEC 61000-4-5 	Yes
Immunity against conducted interference induced by high-frequency fields	
<ul style="list-style-type: none"> • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 	Yes
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> • Limit class A, for use in industrial areas 	Yes; Group 1
<ul style="list-style-type: none"> • Limit class B, for use in residential areas 	Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011
Degree and class of protection	
Degree of protection to EN 60529	
<ul style="list-style-type: none"> • IP20 	Yes
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
Marine approval	
<ul style="list-style-type: none"> • Marine approval 	Yes
Ambient conditions	
Free fall	
<ul style="list-style-type: none"> • Drop height, max. (in packaging) 	0.3 m; five times, in dispatch package
Ambient temperature in operation	
<ul style="list-style-type: none"> • Min. 	-20 °C
<ul style="list-style-type: none"> • max. 	60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical
<ul style="list-style-type: none"> • horizontal installation, min. 	-20 °C
<ul style="list-style-type: none"> • horizontal installation, max. 	60 °C
<ul style="list-style-type: none"> • vertical installation, min. 	-20 °C
<ul style="list-style-type: none"> • vertical installation, max. 	50 °C
Ambient temperature during storage/transportation	

• Min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
• Permissible operating height	-1000 to 2000 m
Relative humidity	
• Permissible range (without condensation) at 25 °C	95 %
Vibrations	
• Vibrations	2G wall mounting, 1G DIN rail
• Operation, checked according to IEC 60068-2-6	Yes
Shock test	
• checked according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
Pollutant concentrations	
— SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
programming	
Programming language	
— LAD	Yes
— FBD	Yes
— SCL	Yes
Cycle time monitoring	
• can be set	Yes
Dimensions	
Width	130 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	585 g
last modified:	16.04.2015