

SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED, 16 DO, 24V DC, 0.5A, 1 X 20 PIN SUM OF OUTPUT CURRENTS 4A/GROUP (8A/MODULE)



Figure similar

| Supply voltage                              |            |
|---|------------|
| Load voltage L+                             |            |
| • Rated value (DC)                          | 24 V       |
| • permissible range, lower limit (DC)       | 20.4 V     |
| • permissible range, upper limit (DC)       | 28.8 V     |
| Input current                               |            |
| from load voltage L+ (without load), max.   | 80 mA      |
| from backplane bus 5 V DC, max.             | 80 mA      |
| Power loss                                  |            |
| Power loss, typ.                            | 4.9 W      |
| Digital outputs                             |            |
| Number of digital outputs                   | 16         |
| Limitation of inductive shutdown voltage to | L+ (-53 V) |
| Switching capacity of the outputs           |            |
| • on lamp load, max.                        | 5 W        |
| Load resistance range                       |            |
| • lower limit                               | 48 Ω       |

|  |                  |
|--|------------------|
| • upper limit                                    | 4 kΩ             |
| <b>Output voltage</b>                            |                  |
| • for signal "1", min.                           | L+ (-0.8 V)      |
| <b>Output current</b>                            |                  |
| • for signal "1" rated value                     | 0.5 A            |
| • for signal "1" minimum load current            | 5 mA             |
| • for signal "0" residual current, max.          | 0.5 mA           |
| <b>Switching frequency</b>                       |                  |
| • with resistive load, max.                      | 100 Hz           |
| • with inductive load, max.                      | 0.5 Hz           |
| • on lamp load, max.                             | 10 Hz            |
| <b>Total current of the outputs (per group)</b>  |                  |
| horizontal installation                          |                  |
| — up to 40 °C, max.                              | 4 A              |
| — up to 60 °C, max.                              | 3 A              |
| vertical installation                            |                  |
| — up to 40 °C, max.                              | 2 A              |
| <b>Cable length</b>                              |                  |
| • shielded, max.                                 | 1 000 m          |
| • unshielded, max.                               | 600 m            |
| <b>Interrupts/diagnostics/status information</b> |                  |
| <b>Alarms</b>                                    |                  |
| • Diagnostic alarm                               | No               |
| <b>Diagnostic messages</b>                       |                  |
| • Diagnostic functions                           | No               |
| • Wire-break                                     | No               |
| • Short-circuit                                  | No               |
| • Fuse blown                                     | No               |
| • missing load voltage                           | No               |
| <b>Diagnostics indication LED</b>                |                  |
| • Rated load voltage PWR (green)                 | No               |
| • Fuse OK FSG (green)                            | No               |
| • Status indicator digital output (green)        | Yes              |
| <b>Potential separation</b>                      |                  |
| <b>Potential separation digital outputs</b>      |                  |
| • between the channels                           | Yes              |
| • between the channels, in groups of             | 8                |
| • between the channels and backplane bus         | Yes; Optocoupler |
| <b>Permissible potential difference</b>          |                  |
| between different circuits                       | 75V DC/60V AC    |

## Isolation

Isolation tested with 500 V DC

## Connection method

required front connector 20-pin

## Dimensions

Width 40 mm

Height 125 mm

Depth 120 mm

## Weights

Weight, approx. 190 g

**last modified:** 12.09.2015