



Ordering data

6SL3210-5BB11-2AV0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.72
Number of phases	1 AC	Offset factor $\cos \varphi$	0.95
Line voltage	200 ... 240 V -10 % +10 %	Efficiency η	0.98
Line frequency	47 ... 63 Hz	Ambient conditions	
Output		Cooling	convection cooling
Number of phases	3 AC	Installation altitude	1000 m (3281 ft)
Rated voltage	230 V	Ambient temperature	
Rated power (HO)	0.12 kW / 0.16 hp	Operation	-10 ... 60 °C (14 ... 140 °F)
Rated power (LO)	0.12 kW / 0.16 hp	Storage	-40 ... 70 °C (-40 ... 158 °F)
Rated current (HO)	0.90 A	Relative humidity	
Rated current (LO)	0.90 A	Max. operation	95 %
Pulse frequency		Communication	
Pulse frequency	2 kHz	Communication	USS, Modbus RTU
Output frequency	0 ... 550 Hz	Standards	
		Compliance with standards	CE, cULus, C-Tick (RCM), KC
		CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s

Ordering data

6SL3210-5BB11-2AV0



Mechanical data

Mounting position Wall mounting / side-by-side mounting

Degree of protection IP20

Size FSA

Net weight 1.10 kg (2.43 lb)

Width 90.0 mm (3.54 in)

Height 150.0 mm (5.91 in)

Depth 145.5 mm (5.73 in)

Inputs/ outputs

Standard digital inputs

Number 4

Digital outputs

Number as relay changeover contact 1

Number as transistor 1

Analog inputs

Number 2 (Can be used as additional digital input)

Analog outputs

Number 1

Connections

Max. motor cable length

Shielded 10 m (33 ft)

Unshielded 50 m (164 ft)