

**COPPER TUBE CRIMPING LUGS ANGLED 90° TYPE A-L
for copper conductors**


Description:

- A-L series lugs angled 90° are manufactured from electrolytic copper tube Cu-OF CW008A conform to UNI EN 13600:2003. The dimensions of the tube are designed to obtain the most efficient electrical conductivity and mechanical strength to resist vibration and pull out.
- Cembre lugs are annealed to guarantee optimum ductility which is an absolute necessity for connectors which will have to withstand the severe deformation arising when compressed and any bending of the palm during installation.
- In applications subject to vibration, terminals still have to perform a reliable connection, annealing plays a vital role in avoiding cracking or breaks between the barrel and palm.
- The presence of an inspection hole facilitates full insertion of the conductor, whilst the barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.
- Lugs are electrolytically tin plated with a minimum thickness of 3µm to avoid oxidation. A-M series lugs form an important part of Cembre crimping systems for power carrying conductors.

Each connector is marked as follows:

- Cembre trade mark and reference number.
- Nature and size of conductor (mm²).
- Ø stud (mm).

Markings:

- *Conform to products norm IEC 61238-1*




- *According to UL 486A standard (file E125401)*

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)
 Tel.: +39 030 36921 - Fax: +39 030 3365766
 Web: www.cembre.com - Email: info@cembre.com

COPPERTUBE CRIMPING LUGS ANGLED 90° TYPE A-L for copper conductors

Sections and Dimensions:



Cond. Size sqmm	Ø Stud mm	Ref.	Dimensions mm						Quantity Box/Bag	
			Øi	B	M	N	A	d		
6	6	A 1-L 6*	3,6	11,0	7,0	6,0	9,5	6,4	2.000/100	
	5	A 2-L 5	4,6	10,0	6,5	6,0	10,5	5,3	1.500/100	
10	6	A 2-L 6	4,6	11,0	7,0	6,0	10,5	6,4	1.500/100	
	8	A 2-L 8	4,6	15,0	9,0	8,0	10,5	8,4	500/100	
16	5	A 3-L 5	5,8	11,5	6,5	6,0	12,0	5,3	1.000/100	
	6	A 3-L 6	5,8	11,5	7,0	6,0	12,0	6,4	1.000/100	
	8	A 3-L 8	5,8	15,0	9,0	8,0	12,0	8,4	1.000/100	
	10	A 3-L 10	5,8	18,0	11,0	10,0	12,0	10,5	500/100	
25	6	A 5-L 6	7,0	14,0	7,0	6,0	13,0	6,4	500/100	
	8	A 5-L 8	7,0	15,0	9,0	8,0	13,0	8,4	500/100	
	10	A 5-L 10	7,0	18,0	11,0	10,0	13,0	10,5	500/100	
35	6	A 7-L 6	8,9	17,0	7,0	6,0	15,5	6,4	500/100	
	8	A 7-L 8	8,9	17,0	9,0	8,0	15,5	8,4	300/100	
	10	A 7-L 10	8,9	19,0	11,0	10,0	15,5	10,5	400/100	
	12	A 7-L 12	8,9	21,0	14,0	12,0	15,5	13,2	300/100	
50	6	A 10-L 6	10,0	19,0	8,0	7,0	16,5	6,4	300/100	
	8	A 10-L 8	10,0	19,0	9,0	8,0	16,5	8,4	300/100	
	10	A 10-L 10	10,0	20,0	11,5	9,5	16,5	10,5	200/50	
	12	A 10-L 12	10,0	21,0	12,0	12,0	16,5	13,2	200/50	
70	8	A 14-L 8	11,3	21,0	9,0	8,0	20,0	8,4	200/50	
	10	A 14-L 10	11,3	21,0	11,0	10,0	20,0	10,5	200/50	
	12	A 14-L 12	11,3	22,0	14,0	12,0	20,0	13,2	150/50	
	16	A 14-L 16	11,3	26,0	18,0	16,0	20,0	17,0	150/50	
95	8	A 19-L 8	13,5	25,0	9,0	8,0	24,5	8,4	100/25	
	10	A 19-L 10	13,5	25,0	11,0	10,0	24,5	10,5	100/25	
	12	A 19-L 12	13,5	25,0	14,0	12,0	24,5	13,2	100/25	
120	10	A 24-L 10	15,2	28,5	11,0	10,0	25,5	10,5	50/25	
	12	A 24-L 12	15,2	28,5	14,0	12,0	25,5	13,2	50/25	
150	10	A 30-L 10	16,7	31,5	13,0	11,0	28,5	10,5	50/25	
	12	A 30-L 12	16,7	31,5	16,0	14,0	28,5	13,2	50/25	
185	10	A 37-L 10	19,2	31,5	13,0	11,0	31,5	10,5	50/25	
	12	A 37-L 12	19,2	31,5	16,0	14,0	31,5	13,2	50/25	
240	10	A 48-L 10	21,1	39,0	13,0	11,0	33,0	10,5	30/15	
	12	A 48-L 12	21,1	39,0	16,0	14,0	33,0	13,2	30/15	
300	240	12	A 60-L 12	23,7	44,0	20,0	14,0	42,0	13,2	20/10
	300									

*Actual conductor section may require a larger lug eg for 120 mm² size use A30-... lug.

*Not UL approved

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: info@cembre.com