

SIEMENS

Data sheet for SINAMICS V20



Figure similar

MLFB-Ordering data 6SL3210-5BB22-2AV0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.72
Number of phases	1 AC	Offset factor $\cos \varphi$	0.95
Line voltage	200 ... 240 V -10 % +10 %	Efficiency η	0.98
Line frequency	47 ... 63 Hz	Ambient conditions	
Output		Cooling	External fan
Number of phases	3 AC	Installation altitude	1000 m (3281 ft)
Rated voltage	230 V	Ambient temperature	
Rated power (HO)	2.20 kW / 3.00 hp	Operation	-10 ... 60 °C (14 ... 140 °F)
Rated power (LO)	2.20 kW / 3.00 hp	Storage	-40 ... 70 °C (-40 ... 158 °F)
Rated current (HO)	11.00 A	Relative humidity	
Rated current (LO)	11.00 A	Max. operation	95 %
Pulse frequency		Communication	
Output frequency		Communication	USS, Modbus RTU
		Standards	
		Compliance with standards	CE, cULus, C-Tick (RCM), KC
		CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3

Overload capability
Low Overload (LO)
110 % rated output current for 60 s, cycle time 300 s
High Overload (HO)
150 % rated output current for 60 s, cycle time 300 s

SIEMENS

Data sheet for SINAMICS V20

MLFB-Ordering data 6SL3210-5BB22-2AV0



Figure similar

Mechanical data		Connections	
Mounting position	Through-hole mounting / wall mounting / side-by-side mounting	Max. motor cable length	
Degree of protection	IP20	Shielded	25 m (82 ft)
Size	FSC	Unshielded	50 m (164 ft)
Net weight	2.50 kg (5.51 lb)		
Width	184.0 mm (7.24 in)		
Height	182.0 mm (7.17 in)		
Depth	169.0 mm (6.65 in)		

Inputs / outputs	
Standard digital inputs	
Number	4
Digital outputs	
Number as relay changeover contact	1
Number as transistor	1
Analog inputs	
Number	2 (Can be used as additional digital input)
Analog outputs	
Number	1